

YOUR END-TO-END CORE RECOVERY PARTNER

Maximize your well production with our flawless core recovery and processing services.

RS4 Equipment Specifications

RS4 Outer Components	Specifications
Outer Dimensions	6.5"
Inner Dimensions	5.25"
Stabilizer Sizes	6.8"-8.44 (Custom Stabilizer upon request)
Make-up Torque (Ft-Lbs)	25,000
Torsional Yield (FT-Lbs)	41,500
Tensile Strength [Over-Pull] (LBS)	561,000
Max deviation Severities Rotating	4°-5° / 100 FT
Max deviation Severities Non-Rotating [Static Bending]	7°-9° / 100 FT
Minimum Fishable Hole Size	7.525"

RS4 Outer Components	RS4 Aluminum	RS4 Steel (IB29)
Steel Inner Tube		<input checked="" type="checkbox"/>
Solid Aluminum Liner		<input checked="" type="checkbox"/>
Channeled Aluminum Liner	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Aerated Aluminum Liner	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Quick View Aluminum Liner	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Solidified Aluminum	<input checked="" type="checkbox"/>	
High pressure rated aluminum	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
CCUS proprietary alluvion	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Telescopic sleeves	<input checked="" type="checkbox"/>	Pending

